

Printing date 02.02.2022 Version number 25 Revision: 02.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: <u>Tank Cure Cleaner</u>

· Article number: P900-00021

· UFI: GN70-M0V6-T00E-J9PD

 \cdot 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment,

services, craftsmen)

SU19 Building and construction work

· Process category PROC19 Manual activities involving hand contact

ERC8c Widespread use leading to inclusion into/onto article (indoor) ERC8f Widespread use leading to inclusion into/onto article (outdoor)

· Article category AC13 Plastic articles

· Application of the substance / the

mixture

See our technical datasheet for application details of this product.

Degreaser

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Poly-Service BV, Hoogeveenenweg 83, NL 2913 LV Nieuwerkerk a/d IJssel

Tel: +31 180 314777, Fax: +31 180 317847

E-mail: info@polyservice.nl

· Further information obtainable

from: Research and Development.

1.4 Emergency telephone

number: Poly-Service BV, Tel: +31 180 314777, E-mail: info@polyservice.nl

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

GHS05 corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

2.2 Label elements

· Labelling according to Regulation

(EC) No 1272/2008 · Hazard pictograms The product is classified and labelled according to the CLP regulation.

GHS05

· Signal word Danger

· Hazard-determining components of

labelling: Alcohols, C10-13, ethoxylated

disodium silicate pentahydrate

Hazard statements H314 Causes severe skin burns and eye damage.

Precautionary statements P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P260 Do not breathe dusts or mists.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/

national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

⋅ PBT: Not applicable.⋅ νPνB: Not applicable.

(Contd. on page 2)



Version number 25 Printing date 02.02.2022 Revision: 02.02.2022

Trade name: Tank Cure Cleaner

(Contd. of page 1)

SECTION 3: Composition/information on ingredients

· 3.2 Chemical characterisation: Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 111-76-2	2-butoxyethanol	2.5 – 10%
EINECS: 203-905-0	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2,	
Index number: 603-014-00-0	H315; Eye Irrit. 2, H319	
Reg.nr.: 01-2119475108-36		
	Alcohols, C10-13, ethoxylated	2.5 – 10%
	🔷 Eye Dam. 1, H318; 🗘 Acute Tox. 4, H302; Skin Irrit. 2, H315	
CAS: 10213-79-3	disodium silicate pentahydrate	2.5 – 10%
EINECS: 229-912-9	♦ Skin Corr. 1B, H314; ♦ STOT SE 3, H335	
CAS: 7320-34-5	tetrapotassium pyrophosphate	1 – 2.5%
EINECS: 230-785-7	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 68649-29-6	phospated alkoxylated fatty alcohol	1 – 2.5%
EC number: 614-696-4	♦ Skin Irrit. 2, H315; Eye Irrit. 2, H319	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation: In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

No further relevant information available.

· 4.2 Most important symptoms and effects, both acute and

delayed

4.3 Indication of any immediate medical attention and special

treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: CO2 or powder. Fight larger fires with alcohol resistant foam.

5.2 Special hazards arising from

the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions: Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for

containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,

sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 3)



Version number 25 Revision: 02.02.2022 Printing date 02.02.2022

Trade name: Tank Cure Cleaner

(Contd. of page 2)

SECTION 7: Handling and storage

· 7.1 Precautions for safe

handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

No special requirements.

Keep container tightly sealed.

· Information about fire - and

explosion protection:

Keep respiratory protective device available.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by

storerooms and receptacles:

· Information about storage in one common storage facility:

Further information about storage

conditions:

· Recommended storage temperature:

5 - 30 \square

Not required.

· 7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Additional information about

No further data: see item 7. design of technical facilities:

Ingredients with limit values that require monitoring at the workplace:

111-76-2 2-butoxyethanol

Short-term value: 246 mg/m³, 50 ppm Long-term value: 98 mg/m³, 20 ppm

Skin

Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

General protective and hygienic

measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of

intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands: Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/

the preparation.

Due to missing tests no recommendation to the glove material can be given for the

product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

· Material of gloves Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material: ≥ 0.3 mm

· Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least

480 minutes (Permeation according to EN 16523-1:2015: Level 6).

· For the permanent contact gloves made of the following materials are suitable:

Nitrile rubber, NBR

As protection from splashes gloves made of the following materials are suitable:

Nitrile rubber, NBR

(Contd. on page 4)

(Contd. of page 3)



Safety data sheet according to 1907/2006/EC, Article 31

Printing date 02.02.2022 Version number 25 Revision: 02.02.2022

Trade name: Tank Cure Cleaner

 Not suitable are gloves made of the following materials: Leather gloves

Strong material gloves

· Eye protection: Tightly sealed goggles

SECTION 9: Physical and chemical properties

Seneral Information on basic physical and chemical properties General Information	•	•
Colour: Odour threshold: Odour threshold: Not determined. pH-value at 20 °C: 13.5 Change in condition Melting point/freezing point: Initial boiling point and boiling range: 100 °C -Flash point: Flammability (solid, gas): Vot applicable. Ignition temperature: 240 °C -Decomposition temperature: Product does not present an explosion hazard. Explosive properties: Product does not present an explosion hazard. Explosion limits: Lower: Upper: 1.1 Vol % Upper: 1.0 & Vol % Vapour pressure at 20 °C: Relative density Vapour density Vapour density Vapour density Evaporation rate Solubility in / Miscibility with water: Pully miscible. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: A mPas (Brookfield, ASTM D1544) Not determined. Vol (2004/42/EC): 10.0 % Solids content: 2.4 %	General Information Appearance:	
Odour threshold: Characteristic Not determined. Pid-value at 20 °C: 13.5 Change in condition Melting point/freezing point: Initial boiling point and boiling range: 100 °C Flash point: 70 °C (Pensky Martens, ASTM D93) Flammability (solid, gas): Not applicable. Ignition temperature: 240 °C Decomposition temperature: Not determined. - Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product does not present an explosion hazard. Explosion limits: Lower: 1.1 Vol % Upper: 10.6 Vol % - Vapour pressure at 20 °C: 1.2 hPa Density at 20 °C: 1.03 g/cm² (DIN 51757, ASTM D 1298) Not determined. Solubility in / Miscibility with water: Fully miscible. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: 2 mPas (Brookfield, ASTM D1544) Kinematic: Not determined. Solubility in / Miscibility: Not determined. Solvent content: Organic solvents: 10.0 % VOC (2004/42/EC): 10.00 % Solids content: 2.4 %		
Odour threshold: Not determined. pH-value at 20 °C: 13.5 Change in condition Melting point/freezing point: Initial boiling point/freezing point: 100 °C Flash point: 70 °C (Pensky Martens, ASTM D93) Flammability (solid, gas): Not applicable. Ignition temperature: 240 °C Decomposition temperature: Not determined. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product does not present an explosion hazard. Explosive properties: 1.1 Vol %		
pH-value at 20 °C: 13.5 Change in condition Melting point/freezing point: Initial boiling point and boiling range: 100 °C Flash point: 70 °C (Pensky Martens, ASTM D93) Flammability (solid, gas): Not applicable. Ignition temperature: 240 °C Decomposition temperature: Not determined. - Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product does not present an explosion hazard. Explosion limits: Lower: 1.1 Vol % Upper: 10.6 Vol % Vapour pressure at 20 °C: 1.2 hPa Density at 20 °C: 1.03 g/cm² (DIN 51757, ASTM D 1298) Not determined. Paquor density Not determined. Solubility in / Miscibility with water: Fully miscible. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: 2 mPas (Brookfield, ASTM D1544) Kinematic: Not determined. Solvent content: Organic solvents: 10.0 % VOC (2004/42/EC): 10.00 % Solids content: 2.4 %		• · · · · · · · · · · · · · · · · · · ·
Change in condition Melting point/freezing point: Initial boiling point and boiling range: 100 °C Flash point: 70 °C (Pensky Martens, ASTM D93) Flammability (solid, gas): Not applicable. Ignition temperature: 240 °C Decomposition temperature: Not determined. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product does not present an explosion hazard. Explosion limits: Lower: 1.1 Vol % Upper: 10.6 Vol % Vapour pressure at 20 °C: 1.2 hPa Density at 20 °C: 1.03 g/cm² (DIN 51757, ASTM D 1298) Not determined. Vapour density Not determined. Solubility in / Miscibility with water: Viscosity: Dynamic at 20 °C: 2 mPas (Brookfield, ASTM D1544) Kinematic: Not determined. Solvent content: Organic solvents: 10.0 % VOC (2004/42/EC): 10.00 % Solids content: 2.4 %		
Melting point/freezing point: Initial boiling point and boiling range: Flash point: Flammability (solid, gas): Ignition temperature: Quo °C Decomposition temperature: Not determined. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product does not present an explosion hazard. Explosion limits: Lower: 1.1 Vol % Upper: 1.6 Vol % Vapour pressure at 20 °C: Relative density Not determined. Vapour density Not determined. Solubility in / Miscibility with water: Viscosity: Dynamic at 20 °C: Partition coefficient: n-octanol/water: Viscosity: Dynamic at 20 °C: 2 mPas (Brookfield, ASTM D1544) Not determined. Solids content: 2.4 %	· pH-value at 20 °C:	13.5
Flammability (solid, gas): Not applicable. Ignition temperature: 240 °C Decomposition temperature: Not determined. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product does not present an explosion hazard. Explosion limits: Lower: 1.1 Vol % Upper: 10.6 Vol % Vapour pressure at 20 °C: 1.2 hPa Density at 20 °C: 1.03 g/cm³ (DIN 51757, ASTM D 1298) Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with water: Fully miscible. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: 2 mPas (Brookfield, ASTM D1544) Kinematic: Not determined. Solubal content: Organic solvents: 10.0 % VOC (2004/42/EC): 10.00 % Solids content: 2.4 %	Melting point/freezing point:	*······
• Ignition temperature: 240 °C • Decomposition temperature: Not determined. • Auto-ignition temperature: Product is not selfigniting. • Explosive properties: Product does not present an explosion hazard. • Explosion limits: Lower: Lower: 1.1 Vol % Upper: 10.6 Vol % • Vapour pressure at 20 °C: 1.2 hPa • Density at 20 °C: 1.03 g/cm³ (DIN 51757, ASTM D 1298) • Relative density Not determined. • Vapour density Not determined. • Vapour density Not determined. • Solubility in / Miscibility with water: Fully miscible. • Partition coefficient: n-octanol/water: Not determined. • Viscosity: Dynamic at 20 °C: 2 mPas (Brookfield, ASTM D1544) • Viscosity: 2 mPas (Brookfield, ASTM D1544) • Solvent content: Organic solvents: 10.0 % • VOC (2004/42/EC): 10.00 % Solids content: 2.4 %	· Flash point:	70 °C (Pensky Martens, ASTM D93)
Decomposition temperature: Not determined. Auto-ignition temperature: Product is not selfigniting. Explosive properties: Product does not present an explosion hazard. Explosion limits: Lower: 1.1 Vol % Upper: 10.6 Vol % Vapour pressure at 20 °C: 1.2 hPa Density at 20 °C: 1.03 g/cm³ (DIN 51757, ASTM D 1298) Not determined. Vapour density Not determined. Vapour density Not determined. Solubility in / Miscibility with water: Fully miscible. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: 2 mPas (Brookfield, ASTM D1544) Kinematic: Not determined. Solvent content: Organic solvents: 10.0 % VOC (2004/42/EC): 10.00 % Solids content: 2.4 %	· Flammability (solid, gas):	Not applicable.
- Auto-ignition temperature: Product is not selfigniting. - Explosive properties: Product does not present an explosion hazard. - Explosion limits:	· Ignition temperature:	240 °C
Explosive properties: Product does not present an explosion hazard. Explosion limits: Lower: 1.1 Vol % Upper: 10.6 Vol % Vapour pressure at 20 °C: 1.2 hPa Density at 20 °C: 1.03 g/cm³ (DIN 51757, ASTM D 1298) Not determined. Vapour density Not determined. Vapour density Not determined. Solubility in / Miscibility with water: Fully miscible. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: 2 mPas (Brookfield, ASTM D1544) Kinematic: Not determined. Solvent content: Organic solvents: 10.0 % VOC (2004/42/EC): 10.00 % Solids content: 2.4 %	· Decomposition temperature:	Not determined.
Explosion limits: Lower: Upper: 10.6 Vol % Vapour pressure at 20 °C: 1.2 hPa Density at 20 °C: 1.03 g/cm³ (DIN 51757, ASTM D 1298) Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with water: Fully miscible. Partition coefficient: n-octanol/water: Viscosity: Dynamic at 20 °C: 2 mPas (Brookfield, ASTM D1544) Kinematic: Not determined. Solvent content: Organic solvents: 10.0 % VOC (2004/42/EC): 10.00 % Solids content: 2.4 %	· Auto-ignition temperature:	Product is not selfigniting.
Lower: Upper: 11.1 Vol % 10.6 Vol % Vapour pressure at 20 °C: 1.2 hPa Density at 20 °C: 1.03 g/cm³ (DIN 51757, ASTM D 1298) Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with water: Fully miscible. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: Kinematic: Vorganic solvents: VOC (2004/42/EC): 10.00 % Solids content: 2.4 %	· Explosive properties:	Product does not present an explosion hazard.
Upper: 10.6 Vol % Vapour pressure at 20 °C: 1.2 hPa Density at 20 °C: 1.03 g/cm³ (DIN 51757, ASTM D 1298) Relative density Not determined. Vapour density Not determined. Evaporation rate Not determined. Solubility in / Miscibility with water: Fully miscible. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: 2 mPas (Brookfield, ASTM D1544) Kinematic: Not determined. Solvent content: Organic solvents: 10.0 % VOC (2004/42/EC): 10.00 % Solids content: 2.4 %	· Explosion limits:	
 · Vapour pressure at 20 °C: · Density at 20 °C: · Relative density · Vapour density · Vapour density · Evaporation rate · Solubility in / Miscibility with water: · Partition coefficient: n-octanol/water: · Viscosity: Dynamic at 20 °C: Kinematic: · Solvent content: · Organic solvents: · VOC (2004/42/EC): 1.2 hPa 1.03 g/cm³ (DIN 51757, ASTM D 1298) Not determined. · Not determined. · Solvent content: Organic solvents: VOC (2004/42/EC): 10.00 % Solids content: 2.4 % 	Lower:	
Density at 20 °C: Relative density Vapour density Not determined. Not determined. Solubility in / Miscibility with water: Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: Kinematic: Viscosity: Organic solvents: Organic solvents: VOC (2004/42/EC): Solids content: 2.4 %	Upper:	10.6 Vol %
Relative density Vapour density Evaporation rate Solubility in / Miscibility with water: Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: Kinematic: Value and the solution of the solu	· Vapour pressure at 20 °C:	1.2 hPa
 Vapour density Evaporation rate Not determined. Solubility in / Miscibility with water: Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: Kinematic: Solvent content: Organic solvents: VOC (2004/42/EC): Solids content: 2.4 % Solvent content: Organic solvents: Organic solvent	· Density at 20 °C:	1.03 g/cm³ (DIN 51757, ASTM D 1298)
 Evaporation rate Not determined. Solubility in / Miscibility with water: Fully miscible. Partition coefficient: n-octanol/water: Not determined. Viscosity:	· Relative density	Not determined.
· Solubility in / Miscibility with water: · Partition coefficient: n-octanol/water: · Viscosity: Dynamic at 20 °C: Kinematic: · Solvent content: Organic solvents: VOC (2004/42/EC): Solids content: 2.4 %		Not determined.
water: Fully miscible. Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: 2 mPas (Brookfield, ASTM D1544) Kinematic: Not determined. Solvent content: Organic solvents: 10.0 % VOC (2004/42/EC): 10.00 % Solids content: 2.4 %	· Evaporation rate	Not determined.
Partition coefficient: n-octanol/water: Not determined. Viscosity: Dynamic at 20 °C: Kinematic: Vot determined. Solvent content: Organic solvents: VOC (2004/42/EC): Solids content: 2.4 %		
· Viscosity: Dynamic at 20 °C: Example 20 °C: Examp	water:	Fully miscible.
Dynamic at 20 °C: Kinematic: Not determined. Solvent content: Organic solvents: VOC (2004/42/EC): Solids content: 2.4 %	· Partition coefficient: n-octanol/water:	Not determined.
Organic solvents: 10.0 % VOC (2004/42/EC): 10.00 % Solids content: 2.4 %	Dynamic at 20 °C:	
Organic solvents: 10.0 % VOC (2004/42/EC): 10.00 % Solids content: 2.4 %	· Solvent content:	
VOC (2004/42/EC): 10.00 % Solids content: 2.4 %		10.0 %
• 9.2 Other information No further relevant information available.	Solids content:	2.4 %
	· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

10.2 Chemical stability
 Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous

reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available. • 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 5)



Version number 25 Revision: 02.02.2022 Printing date 02.02.2022

Trade name: Tank Cure Cleaner

(Contd. of page 4)

· 10.6 Hazardous decomposition

No dangerous decomposition products known. products:

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

Based on available data, the classification criteria are not met. · Acute toxicity

· LD/LC50 values relevant for classification:

· Compor	nents	Туре	Value	Species	
ATE (A	cute To	oxicity Estimates)			
Oral	LD50	3,737 mg/kg			
Dermal	LD50	4,000 mg/kg (rab)			

	•		
	111-76-2 2-butoxyethanol		
Oral	LD50	1,480 mg/kg (Rat)	
Dermal	LD50	400 mg/kg (rab)	
7320-34	l-5 tetr	apotassium pyrophosphate	
Oral	LD50	> 2,000 mg/kg (Mouse)	

· Primary irritant effect:

· Skin corrosion/irritation Causes severe skin burns and eye damage.

· Serious eye damage/irritation Causes serious eye damage.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· Additional toxicological information:

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

· Germ cell mutagenicity Based on available data, the classification criteria are not met. · Carcinogenicity Based on available data, the classification criteria are not met. · Reproductive toxicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. · STOT-single exposure · STOT-repeated exposure Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. · Aspiration hazard

SECTION 12: Ecological information

· 12.1 Toxicity

· vPvB:

· Aquatic toxicity: No further relevant information available.

· Type of test Effective concentration Method Assessment **ATE (Acute Toxicity Estimates)**

Inhalative LC50/4 h 110 mg/l

12.2 Persistence and

degradability No further relevant information available. No further relevant information available. · 12.3 Bioaccumulative potential · 12.4 Mobility in soil No further relevant information available.

· Additional ecological information:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for · General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water

course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised. Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the

aqueous waste, emptied into drains, is only low water-dangerous.

· 12.5 Results of PBT and vPvB assessment · PBT: Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

 Recommendation Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

Not applicable.

(Contd. on page 6)



Printing date 02.02.2022 Version number 25 Revision: 02.02.2022

Trade name: Tank Cure Cleaner

(Contd. of page 5)

· European waste catalogue

HP4 | Irritant - skin irritation and eye damage

· Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information	
14.1 UN-Number	
· ADR/RID/ADN, IMDG, IATA	UN2735
14.2 UN proper shipping nameADR/RID/ADNIMDG, IATA	2735 AMINES, LIQUID, CORROSIVE, N.O.S. (disodium silicate pentahydrate) AMINES, LIQUID, CORROSIVE, N.O.S. (disodium silicate
· 14.3 Transport hazard class(es)	pentahydrate)
· ADR/RID/ADN · Class · Label	8 (C7) Corrosive substances. 8
· IMDG, IATA · Class · Label	8 Corrosive substances. 8
· 14.4 Packing group · ADR/RID/ADN, IMDG, IATA	II
· 14.5 Environmental hazards:	
· Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Segregation groups · Stowage Category · Segregation Code	Warning: Corrosive substances. 80 F-A,S-B Alkalis A SG35 Stow "separated from" SGG1-acids
· 14.7 Transport in bulk according to Annex II of I and the IBC Code	Marpol Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· Transport category · Tunnel restriction code	2 E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.S. (DISODIUM SILICATE PENTAHYDRATE), 8, II

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances -

ANNEX I

None of the ingredients is listed.

(Contd. on page 7)



Version number 25 Printing date 02.02.2022 Revision: 02.02.2022

Trade name: Tank Cure Cleaner

(Contd. of page 6)

· REGULATION (EC) No 1907/2006

ANNEX XVII Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

National regulations:

· Technical instructions (air):

Class Share in % NK 10.0

· 15.2 Chemical safety

assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H302 Harmful if swallowed Relevant phrases

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

· Classification according to Regulation (EC) No 1272/2008		
Skin corrosion/irritation	The classification of the mixture is generally based on the calculation method using	
Serious eye damage/eye irritation	substance data according to Regulation (EC) No 1272/2008.	

· Department issuing SDS:

Research and Development

· Contact:

G. Lok (tel +31 0180 314777, e-mail info@polyservice.nl)

· Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer

(Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement

Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1B: Skin corrosion/irritation – Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Literature data and/or investigation reports are available through the manufacturer. Sources:

* Data compared to the previous version altered.